

**Vue d'ensemble**

- M12, female, A-coded; 12-poles; PVC, 500 cm, free cable end
- Head A: IP65, IP66K, IP67
- Cable: good resistance against chemicals


**Caractéristiques techniques**
**Side A**

Head A: Connection	M12
Head A: Angle cable outlet	0°
Head A: Gender	Female
Head A: Coding	A
Head A: No. of poles	12
Head A: LED	No
Head A: Width across flats	AF13
Head A: Tightening torque	0,6 Nm
Head A: Knurled nut material	Zinc-pressure die casting, surface Ni
Head A: Body color	Black
Head A: Gasket material	FKM
Labeling sleeve side A	Yes

**Side B**

Head B: Connection	Open-ended wires
Labeling sleeve side B	Yes

**Cables**

Cable length	500 cm
Length tolerance	± 7,5 cm
Stripping length	80 mm
Shielded	No
Conductor structure	18 × 0,1 mm
AWG	26
External sheath: Material	PVC
External sheath: Color	Black
Cable diameter	6 mm ± 5%
Wire cross section	0,14 mm <sup>2</sup>

**Cable**

Cable: Temperature range (mobile)	- 5 ...+ 70 °C
Cable: Temperature range (fixed)	- 30 ...+ 70 °C
Shielded	No
Bending radius (fixed)	60 mm
Number of wires	12
Number and diameter of wires	12x0,14
Length tolerance	± 7,5 cm
Cable length	500 cm
AWG	26
Bending radius (mobile)	min. 10 × outer diameter
Cable weight	approx. 55 g/m

**Cable**

Conductor structure	18 × 0,1 mm
Cable diameter	6 mm ± 5%
Conductor: Material	Copper, bare
External sheath: Material	PVC
Insulation: Material	PVC
No. of bending cycles (C-track)	Cycles
Nominal voltage	300 V
Paired stranding	No
Single wire diameter	0,1 mm
Cable: Test voltage	1,5 kV
Total stranding	3 wires strand, above that 9 wires strand in opposite direction
Wire cross section	0,14 mm <sup>2</sup>
Wire processing	No
Wire diameter incl. isolation	1 mm ± 5%
External sheath: Color	Black

**Données électriques**

Operating voltage	max. 30 V AC/DC
Nominal voltage	300 V
Contact resistance	max. 30 mOhm
Operating current per contact	max. 1,5 A

**Données mécaniques**

Head A: Degree of protection	IP65, IP66K, IP67
Bending radius (mobile)	min. 10 × outer diameter
No. of bending cycles (C-track)	Cycles

**Conditions ambiantes**

Temperature range (mobile)	- 5 ...+ 70 °C
Temperature range (fixed)	- 25 ...+ 70 °C
Cable: Temperature range (fixed)	- 30 ...+ 70 °C
Dragchain capable	No
Head A: Chemical resistance	No
Head A: Flame resistance	HB (UL 94)
Head A: Oil resistance	ASTM 1 oil, mineral oils, limited to hydraulic oils
Head A: Acid and alkali resistant	No

**Caractéristiques techniques**

**Conditions ambiantes**

Head A: Pollution degree	3
Cable: Chemical resistance	Good
Cable: Oil resistance	Good

**Conditions ambiantes**


Cable: Silicone-free	Oui
----------------------	-----

**Commercial data**

Eclass	27060311
--------	----------


**Side A**

**Technical drawing**




**Side B**

**Technical drawing**



**Coding**



**Schéma de raccordement**

1 )	BN
2 )	BU
3 )	WH
4 )	GN
5 )	PK
6 )	YE
7 )	BK
8 )	GY
9 )	RD
10 )	VT
11 )	GY PK
12 )	RD BU